



VALO MINI

Typology

Compact adjustable LED downlight with integrated driver.

Features

Classic spot with 75 mm cut-out and 40° aperture.
Available in warm and natural light versions.
Compact and easy to install.
Tilt Adjustability 30°.
Non removable built-in power supply.

Installation

Complete with springs for easy fastening into false ceilings.

Material


Heat resistant, anti-yellowing plastic body.

220-240 Vac	Ra 80		15000 h	IP20 VI IP43 VO	Wire	-25°C +35°C	RG0	BASIC	
	G2								

Characteristic data

Power	7 W	Beam	40°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	20	Optical compartment IP	43	Flux	650 lm
PF	0.5	Tc	4000 K	Ra	80	LED Warranty	G2
Axis	735 cd	RG	RG0				

Dimensional characteristics



Ø	90 mm
H	40 mm

Cutting hole	72
--------------	----

Lighting and photometric features

Beam opening	40°
Flux	650 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B30
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	7 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0.5
Operating temperature	-25°C / +35°C

Photometry

EuLumDat file on the site

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC (Compatibilità Elettromagnetica)
2014/35/EU * LVD (Bassa Tensione)
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Barcode single item	8011905987718
Number of pieces multiple pack	20
Barcode multiple pack	8011905990169

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products