



MULTI GU10LL

Typology

New generation LED lamps with COB technology.

Features

Lamps built to achieve a particularly long life: 50,000h, especially required in public or premium projects.

The lens is specially designed to obtain directionality of light, a clean beam and lower glare effect.

Material

Thermally conductive compartment for housing the electronic components: optimization of heat dissipation and greater safety for the user.

Notes

Do not use with dimmer.



Characteristic data

| | | | | | | | |
|-------|------|--------------|-------|----------|--------|-------|-------------|
| Power | 6 W | Beam | 38° | Dimmable | No | Input | 220-240 Vac |
| Base | GU10 | IP | 20 | Flux | 700 lm | Tc | 4000 K |
| Ra | >80 | LED Warranty | G5h24 | Axis | 850 cd | | |

Dimensional characteristics

| | |
|---|-------|
| ø | 45 mm |
| H | 55 mm |

Lighting and photometric features

| | |
|---|--------------------|
| Beam opening | 38° |
| Flux | 700 lm |
| CCT nominal colour temperature | 4000 K |
| Colour of the light | Natural light |
| Colour rendering index | >80 |
| Lifespan | 50000 h |
| LED lifespan | L70B50 |
| Trigger time | <0,2 s |
| Heating time up to 60% of full efficiency | Instant Full Light |
| Mercury | 0 mg |

Electrical characteristics

| | |
|------------------------------------|---------------|
| Rated power | 6 W |
| Input voltage | 220-240 Vac |
| Frequency | 50 Hz |
| Dimmable | No |
| Operating temperature | -25°C / +35°C |
| Equivalence with incandescent lamp | 96 |
| Operating position | 360° |

Photometry

EuLumDat file on the site

Other Infotech

| | |
|-----------|-----|
| Reflector | Yes |
|-----------|-----|

LED Warranty

| | |
|-------|---|
| G5h24 | Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|-------|---|

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC (Compatibilità Elettromagnetica)
2014/35/EU * LVD (Bassa Tensione)
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

| | |
|--------------------------------|---------------|
| Barcode single item | 8011905979928 |
| Number of pieces multiple pack | 10 |
| Minimum order quantity | 10 |
| Minimum packaging | 10 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products