



## Surface Spot Selena

- Stylish and compact surface mounted spot
- Clean "twist-and-lock" mounting system
- High quality full metal body
- Standard CRI 90



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
On-Off, Adjustable							
541003589600	LEDSpotRA-Selena-E 5W-930-55D-WH	Halogen 35W	4.8	400	83	3000	0.22

## Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
541003589600	LEDSpotRA-Selena-E 5W-930-55D-WH	94051190	61x61x120	0.26	6941497787132	1

### Technical Specifications

Lifetime (L70)	50,000 h
Lifetime (L80)	30,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	On-Off
Beam angle	55°
Maximum tilt angle	90°
Finishing	Matte White
Colour rendering index (CRI)	≥ 90
Degree of protection (IP)	IP20
Impact strength	IK02
Protection class	II
Risk group (EN 62471)	RG1
With control gear	Yes
Glow wire test	650°C

### Electrical Supply

Frequency	50/60 Hz
Nominal voltage	220-240 V
DC input voltage	See catalogue appendix
Connection	Specifications

### Mechanical Properties

Housing material	Aluminium
Optical material	Polycarbonate

### Ambient Conditions


Operating temperature	-10-+40°C
Application temperature	+25°C
Storage environment	-25-+50°C

**5 YEARS WARRANTY**



## Dimensional Drawing (mm)

LEDSpotRA-Selena-E 5W



## Photometric Data

