

PS230 | Cluster | 2m | Black Wire | 2400K WW+



Article number:	012-003	
CHANGED_LAST:	21-06-2022	
Brand:	Tronix Lighting	
Туре:	Cluster Lights	
ETIM Group:	EG000027 - Luminaires	
ETIM Classes:	EC002761 - Festive lighting	
SYNONYM:	Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set	



Page: 1/3















Feature

Adde:ChainlightFailure rate at median useful life of 50,000 htt 25 °C ambient (25 °C amb				
Lamp type:LED not exchangeableDegree of protection (IP):IP65With light source:YesProtection class:IIColour:OtherFire resistance according to UL94:CVoltage type:ACColour of light:WhiteNominal voltage:230 - 230 VPower facto:0.95Connected load:7 WWhite0 mmBattery power supply:NoHeight/depth:0 mmSuitable for outdoor use:YesTotal length:2 mWith power bridge:NoDiameter:0 mmConnectable:YesType of wring:Through wring includedType of control gear:LED operating device voltage-controlledNumber of poles:2Energy efficiency class of the built-in lam:A++, A+, A(LED)Connection type:0 therLumen maintenance at median useful life of0%MM	Model:	Chainlight		0 %
With light source:YesProtection class:IIColour:OtherFire resistance according to UL94CVoltage type:ACColour of light:WhiteNominal voltage:230 - 230 VPower factor:0.95Connected load:7 WWidth:0 mmBattery power supply:NoHeight/depth:0 mmSuitable for outdoor use:YesTotal length:2 mWith power bridge:NoDiameter:0 mmConnectable:YesTotal length:2 mConnectable:YesTotal length:1 mough wring includedType of control gear:LED operating device voltage-controlledNumber of poles:2Energy efficiency class of the built-in lame:A++, A+, A (LED)Connection type:OtherRated life time L70/B50 at 25 °C:2000 hcommerial, christmas or both:NALumen maintenance at median useful life of0 %Conductor consectorNA	Number of light centres:	120	Constant light output (CLO):	No
Colour:OtherFire resistance according to UL94:CNotiage type:ACColour of lightWhiteNominal voltage:30 ~ 230 VPower fact:0.95Connected load:7 WWitti0 mmConnected load:7 WMoninal voltage:0 mmBattery power suppi:NoTotal length:2 mSuitable for outdoor use:YesTotal length:0 mmMoninal voltage:VesDiamete:0 mmConnectable:YesTotal length:2 mMoninal voltage-controlledNumber of pole:2Moninal voltage:NoConductor cross setti0.5 mm²Energy efficiency class of the built-in lame:A++, A+, A (LED)Connection type:OtherRated life time L70/B50 at 25°C:2000 hcommerial, christmas or bottiNALumen maintenance at median useful life0 %Connection type:Na	Lamp type:	LED not exchangeable	Degree of protection (IP):	IP65
ACColour of lightWhiteNominal voltage type:ACColour of lightWhiteNominal voltage:230 ~ 230 VPower factor:0.95Connected load:7 WWidth:0 mmBattery power supply:NoHeight/depth:0 mmSuitable for outdoor use:YesTotal length:2 mWith power bridge:NoDiameter:0 mmConnectable:YesType of wiring:Through wiring includedType of control gear:LED operating device voltage-controlledNumber of poles:2Energy efficiency class of the built-in lamp:A++, A+, A (LED)Connection type:OtherRated life time LT0/B50 at 25 °C:20000 hcommerial, christmas or both:NA	With light source:	Yes	Protection class:	II
Nominal voltage:230 ~ 230 VPower factor:0.95Connected load:7 WWidth:0 mmBattery power supply:NoHeight/depth:0 mmSuitable for outdoor use:YesTotal length:2 mWith power bridge:NoDiameter:0 mmConnectable:YesType of wirnig:Through wiring includedConnectable:LED operating device voltage-controlledNumber of poles:2Exchangeable control gear:NoConductor cross section:0.5 mm²Energy efficiency class of the built-in lamp:A++, A+, A (LED)Commerial, christmas or both:NALumen maintenance at median useful life of0 %NA	Colour:	Other	Fire resistance according to UL94:	С
Connected load7 WWidth:0 mmBattery power supplyNoHeight/depth:0 mmSuitable for outdoor use:YesTotal length:2 mWith power bridge:NoDiameter:0 mmConnectable:YesType of wirns:Through wiring includedConnectable:VesType of wirns:1 mough wiring includedType of control ges:LED operating device voltage-controlledNumber of poles:2Energy efficiency class of the built-in lame:A++, A (LED)Connection type:OtherRated life time L70/B50 at 25°C:2000 hcommerial, christmas or both:NALumen maintenance at median useful life of0 %Stated life time L70Stated life time L70	Voltage type:	AC	Colour of light:	White
Battery power supplyNoHeight/depty0 mmSuitable for outdoor useYesTotal lengts2 mWith power bridgeNoDiameter0 mmConnectableYesType of wiringThrough wiring includedConnectableLED operating device voltage-controlledNumber of poles2Exchangeable control gearNoConductor cross section0.5 mm²Energy efficiency class of the built-in lamuA++, A (LED)Commerial, christmas or bothNALumen maintenance at median useful life of0 %Commerial, christmas or bothNA	Nominal voltage:	230 ~ 230 V	Power factor:	0.95
Suitable for outdoor use:YesTotal length:2 mMith power bridge:NoDiameter:0 mmConnectable:YesType of wiring:Through wiring includedType of control gear:LED operating device voltage-controlledNumber of poles:2Exchangeable control gear:NoConductor cross section:0.5 mm²Energy efficiency class of the built-in lamp:A++, A+, A (LED)Conmercial, christmas or both:NARated life time L70/B50 at 25°C:2000 hcommercial, christmas or both:NA	Connected load:	7 W	Width:	0 mm
With power bridgeNoDiameter0 mmConnectableYesType of wiring:Through wiring includedType of control gear:LED operating device voltage-controlledNumber of poles:2Exchangeable control gear:NoConductor cross section:0.5 mm²Energy efficiency class of the built-in lamp:A++, A+, A (LED)Conmercial, christmas or both:NARated life time L70/B50 at 25°C:2000 hcommercial, christmas or both:NA	Battery power supply:	No	Height/depth:	0 mm
KinceYesType of wiring:Through wiring includedType of connectable:KED operating device voltage-controlledNumber of poles:2Exchangeable control gear:NoConductor cross section:0.5 mm²Energy efficiency class of the built-in lamp:A++, A+, A (LED)Connection type:OtherRated life time L70/B50 at 25°C:2000 hcommerial, christmas or both:NALumen maintenance at median useful life of0 %ContextContext	Suitable for outdoor use:	Yes	Total length:	2 m
Type of control gear: LED operating device voltage-controlled Number of poles: 2 Exchangeable control gear: No Conductor cross section: 0.5 mm² Energy efficiency class of the built-in lamp: A++, A+, A (LED) Connection type: Other Rated life time L70/B50 at 25 °C: 2000 h commerial, christmas or both: NA Lumen maintenance at median useful life of 0 % 0 % Conductor cross section: Conductor cross section:	With power bridge:	No	Diameter:	0 mm
Exchangeable control gear: No Conductor cross section: 0.5 mm² Energy efficiency class of the built-in lamp: A++, A+, A (LED) Connection type: Other Rated life time L70/B50 at 25 °C: 2000 h commerial, christmas or both: NA Lumen maintenance at median useful life of 0 %	Connectable:	Yes	Type of wiring:	Through wiring included
Energy efficiency class of the built-in lamp: A++, A+, A (LED) Connection type: Other Rated life time L70/B50 at 25 °C: 2000 h commerial, christmas or both: NA Lumen maintenance at median useful life of 0 % 0 % NA	Type of control gear:	LED operating device voltage-controlled	Number of poles:	2
Rated life time L70/B50 at 25 °C: 20000 h commerial, christmas or both: NA Lumen maintenance at median useful life of 0 %	Exchangeable control gear:	No	Conductor cross section:	0.5 mm²
Lumen maintenance at median useful life of 0 %	Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Connection type:	Other
	Rated life time L70/B50 at 25 °C:	20000 h	commerial, christmas or both:	NA
		0 %		

Packaging data

Weight	620 gr
Width	100 mm
Height	130 mm
Length	230 mm
Customs code	9405310000

Page: 2/3
























Page: 3/3

SHARE









