



## 3D ball | 50cm | white cable | 6500K CW+ & flash 6500K CW



Decorative light balls from Tronix Lighting feature powerful lighting in a variety of atmospheric light colors. Each motif is equipped with a plug that you can easily combine with the Pro System Modular 230V system. This not only makes it possible to connect multiple motifs to a line, but also allows you to combine light motifs with light strings, icicle curtains and more.

### Features

- IP65
- Available in various sizes, ideal for events and tree or street lighting
- Steel construction for a longer life and ease of use
- Compatible with Pro System Modular 230V and accessories
- Easy installation with suitable main cables
- Foldable design for easy handling and transport
- 6500K and FLASH 6500K to combine with our range of season and party lighting

Article number: 571-016

CHANGED\_LAST: 16-01-2024

Brand: Tronix Lighting

Type: 3D motifs

ETIM Group: EG000027 - Luminaires

ETIM Classes: EC002761 - Festive lighting

SYNONYM: Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set





## Feature

Model:	Decorative image	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Number of light points:	189	Constant light output (CLO):	No
Lamp type:	LED not exchangeable	Degree of protection (IP):	IP65
With light source:	Yes	Protection class:	II
Colour:	White	Fire resistance according to UL94:	C
Voltage type:	AC	Colour of light:	White
Nominal voltage:	230 ~ 230 V	Power factor:	0.95
Connected load:	10 W	Width:	0 mm
Battery power supply:	No	Height/depth:	0 mm
Suitable for outdoor use:	Yes	Total length:	0 m
With power bridge:	No	Diameter:	500 mm
Couplable:	Yes	Type of wiring:	Through wiring included
Type of control gear:	LED operating device voltage-controlled	Number of poles:	2
Exchangeable control gear:	No	Conductor cross section:	0.5 mm <sup>2</sup>
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Connection type:	Other
Rated life time L70/B50 at 25 °C:	25000 h	commercial, christmas or lightdesign:	NA
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %		

## Packaging data

Weight	3.26 kg
Width	535 mm
Height	100 mm
Length	535 mm
Customs code	9405114090

