

# TYTAN 2 LED 1150MM 9050LM 840 IP66 55W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	909733
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Nominal power [W]:</b>	55
<b>Luminous flux [lm]*:</b>	9050
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

TYTAN 2 LED is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

# TYTAN 2 LED 1150MM 9050LM 840 IP66 55W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	909733	Mounting dimensions [mm]:	800
EAN:	5905963909733	Impact resistance:	IK09
Light source:	LED module	Ingress protection:	IP66
Nominal power [W]:	55	Mounting version:	surface, suspended
Rated power of the luminaire [W]:	59.30	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Net weight of the luminaire [kg]:	1.420
Frequency [Hz]:	50 - 60	Mark D:	yes
Luminous flux [lm]:	9050	Category type:	battens
Luminous efficacy [lm/W]:	153	Category of application:	industrial
Energy efficiency class:	C	AC voltage range [V]:	220 - 240
Electrical protection class:	I	LED lifespan L70B50 [h]:	109000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	69000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	34000
SDCM:	≤ 3	ETIM class:	EC000109
Power factor:	0.95	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Exchangeable source:	yes	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	<a href="#">127/2023</a>
Diffuser type:	MAT	PZH certificate:	<a href="#">B-BK-60212-0152/20</a>
Material of the body:	PC	HACCP:	<a href="#">852/2004</a>
Colour of the body:	grey	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	1152/85/80	ENEC Certificate:	<a href="#">0310/ENEC/23</a>

## LIGHT CURVES



# TYTAN 2 LED 1150MM 9050LM 840 IP66 55W

DETAILED CARD

## TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

# TYTAN 2 LED 1150MM 9050LM 840 IP66 55W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
941375	TYTAN 2 LED 1150mm 2650lm 840 - moduł świetlny
941382	TYTAN 2 LED 1150mm 4550lm 840 - moduł świetlny
941405	TYTAN 2 LED 1450mm 5650lm 840 - moduł świetlny
941412	TYTAN 2 LED 1450mm 7050lm 840 - moduł świetlny
941429	TYTAN 2 LED 1450mm 11300lm 840 - moduł świetlny
941856	TYTAN 2 LED 1150mm 2450lm 830 - moduł świetlny
941863	TYTAN 2 LED 1150mm 4150lm 830 - moduł świetlny
941870	TYTAN 2 LED 1150mm 7300/8400lm 830 - moduł świetlny
941887	TYTAN 2 LED 1450mm 5250lm 830 - moduł świetlny
941894	TYTAN 2 LED 1450mm 6550lm 830 - moduł świetlny
941900	TYTAN 2 LED 1450mm 10500lm 830 - moduł świetlny
942358	TYTAN 2 LED 1150mm 2650lm 850 - moduł świetlny
942365	TYTAN 2 LED 1150mm 4550lm 850 - moduł świetlny
942372	TYTAN 2 LED 1150mm 7850/9050lm 850 - moduł świetlny
942389	TYTAN 2 LED 1450mm 5650lm 850 - moduł świetlny
942396	TYTAN 2 LED 1450mm 7050lm 850 - moduł świetlny
942402	TYTAN 2 LED 1450mm 11300lm 850 - moduł świetlny
908231	TYTAN LED - holder



M16 stuffing box plug various PA black  
M-16 - BPM-21 (60000006)

Card creation date: 24 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 127/2023