



ELLIPSOIDAL HIGH POWER

Typology

Range of high power LED lamps with SMD technology and high efficiency chip. The ellipsoidal shapes recalls that of discharge lamps that are replaced by the same fixtures.

The 1800K and 2400K versions are specially designed to produce a "sodium effect": the extremely warm light colour is perfect for lighting stone buildings and ancient squares.

Features

Innovative technological solution: the ballast has been separated into two parts to create a wide cooling zone and ensure long life.

50W and 70W versions are equipped with an E27 cap and and E40 adapter. PF: 0.95.

Material

Thermally conductive plastic body and dissipator; opal polycarbonate anti-glare screen.

Applications

Suitable for outdoor use inside suitable fixtures.

Notes

Do not use with dimmer.

It can be used in closed fixtures.

30W and 40W: lamps suitable for installation and use in residential, commercial and light industrial environments, in systems with "Category I" of impulse withstand in compliance with CEI EN 64-8/4 (IEC 60364-4-44).

In case of installation in public areas, it is advisable to use overvoltage surge protection.


50W and 70W: models are designed to withstand voltage peaks up to 6KV.

220-240 Vac	Ra >80		20000 h	IP20	E27 / E40	-25°C / +35°C		BASIC	
G2									

Characteristic data

Power	50 W	Beam	300°	Dimmable	No	Input	220-240 Vac
Base	E27/E40	IP	20	Flux	5960 lm	PF	0,95
Tc	3000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	110 mm
H	269 mm

Lighting and photometric features

Beam opening	300°
Flux	5960 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	20000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	50 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,95
Energy efficiency class	E
Number of cycles	40000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	325

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC (Compatibilità Elettromagnetica)
2014/35/EU * LVD (Bassa Tensione)
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Barcode single item	8011905950828
Number of pieces multiple pack	10
Barcode multiple pack	8011905952068