



HB5 - HIGH BAY

Typology

Suspended luminaire for installation in large commercial and industrial spaces; uses highly efficient SMD technology.
Available in 3 sizes and 4 wattages.
Polycarbonate or aluminium reflector available with accessory code.

Features


The optical unit is integrated into the aluminium body for perfect heat dissipation.
Equipped with 4kV voltage surge protection.
Arrangement for remote-controlled sensor, see accessory codes.
Via the remote control it is possible to switch the luminaire on and off, dim and select the lighting mode with motion detection or room brightness detection.

Installation

Equipped with a mounting ring for suspension installation.
For surface mounting, order bracket accessory code.

Material

Grooved die-cast aluminium for heat dissipation.
Suitable for use in dusty and humid environments due to its high IP rating.




220-240 Vac	Ra 80		100000 h	IP65	IK08	Wire	-25°C +35°C	RG1	PRO
	90°	G5h24	FLICKER FREE						

Characteristic data

Power	200 W	Beam	90°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	65	Flux	32000 lm	PF	0.9
Tc	4000 K	Ra	80	LED Warranty	G5h24	Axis	16200 cd
IK	IK08	RG	RG1				

Dimensional characteristics



Ø	360 mm
H	84 mm
H2	120 mm

Lighting and photometric features

Beam opening	90°
Flux	32000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	80
Lifespan	100000 h
LED lifespan	L70B50

Electrical characteristics

Rated power	200 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0.9
Weighted energy consumption	200 kWh/1000h
Energy efficiency class	This product contains a light source of energy efficiency class "B"
Operating temperature	-25°C / +35°C

Photometry

EuLumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G5h24	<p>Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.</p>
-------	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Barcode single item	8011905015015
Minimum order quantity	1