



## STAGNA S2T L2 IP65 - 50000H

### Typology

Waterproof linear ceiling light with G13 connection for 2 TUBOLED. Complete with 50,000h Tuboled.

### Features


Quick opening mechanism for wiring.

### Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation. Every batten is equipped with brackets.

### Material


Polycarbonate body: transparent polycarbonate screen equipped with internal fins for flow recovery and emission optimization.



### Characteristic data

Dimmable	No	Input	220-240 Vac	Base	G13	IP	65
Flux	3100 lm	PF	0,9	LED Warranty	G4	IK	IK07

### Dimensional characteristics



L	1275 mm
L1	95 mm
H	60 mm

### Lighting and photometric features

Flux	3100 lm
Lifespan	50000 h

## Electrical characteristics

Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,9
Operating temperature	-25°C / +35°C

## Photometry

EulumDat file on the site

## LED Warranty

G4	undefined
----	-----------

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-1:2022  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

Barcode single item	8011905017200
Number of pieces multiple pack	10
Minimum order quantity	10