



DR111 - WF

Typology LED DR111.

Features

Reflector Effect: coverage of the light source makes these lamps similar to traditional halogen sources they are intended to replace.

High reflectance metal reflector.

Base in termoresistent plastic material.

Lightness is an important feature of this product: ideal for use on any type of ceiling

ApplicationsProfessional directional lighting: ideal for use in shops and in areas where accent lighting is required.

Usage information

Compatible with 12V AC 50/60Hz output electromagnetic transformers. Do not use this item with electronic transformers for halogen lamps. Do not use with dimmer.

Can be used with Duralamp's drivers for LED: maximum load should not exceed 55% of the rated power of the transformer.

12 Vdc

Ra 80



25000 h

IP20

G53

-25°C +35°C








Data sheet code: L8083W

G2

Characteristic data

Power	11 W	Beam	30°	Dimmable	No	Input	12 Vdc
Base	G53	IP	20	Flux	825 lm	PF	0,70
Tc	3000 K	Ra	80	LED Warranty	G2	Axis	1550 cd

Dimensional characteristics



Ø	111 mm
Н	65 mm



Data sheet code: L8083W



Lighting and photometric features

Beam opening	30°
Flux	825 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	11 W
Input voltage	12 Vdc
Dimmable	No
Power factor (PF)	0,70
Weighted energy consumption	11 kWh/1000h
Energy efficiency class	G
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	88
Operating position	360°

Other Infotech

R	Reflector	Yes	

LED Warranty

62	Up to 2 years
	(4000h/year) *4000h = 11h a day x 365 days.
	Without limitations on the duration of use for the first year, provided the observance of
	the installation conditions.

European Directives

Product standards

2009/125/EC * Ecodesign	CEI EN 55015:2020 (+A11:2020)
2011/65/EU * RoHS	CEI EN 62838:2016 (+EC:2018)
2012/19/EU * RAEE	CEI EN 61000-3-2:2019 (+A1:2021)
2014/30/EU * EMC	CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
2015/863 * Amending RoHS	CEI EN 61547:2010
2017/1369 * Regulation for Energy Labelling	CEI EN 62031:2021 (+A11:2022)
2019/2015 * Regulation for Energy Labelling	CEI EN 62471:2010
2019/2020 * Regulation for Ecodesign	IEC/TR 62471-2:2009
2021/340 * Amending Reg. Energy Labelling	CEI 34-141:2014
2021/341 * Amending Reg. Ecodesign	

Logistics data

Item net weight	117 gr
Barcode single item	8011905003692
Number of pieces multiple pack	50
Minimum order quantity	10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

