



## Spot | White | Cut Out Ø90-95mm | 9W | 4000K | Dim.

Article number: 136-106

These Downlights are the newest generation of LED Downlights. The design of this Downlight-Spot, is just like a LED downlight, but like a spot, it has a reflector.

### Features

- Terminal block for a dustproof connection to 220-240V
- Long service life of 44,000 operating hours
- Thermal conductive plastic coated aluminum housing with V-0 flame rating (flame goes out within 10 seconds)
- Modern design suitable for many applications in suspended ceilings or other hollow ceiling systems
- Triac dimmable (see for suitable dimmers related products)

## Specifications

|                   |                       |               |                       |                    |                            |
|-------------------|-----------------------|---------------|-----------------------|--------------------|----------------------------|
| Type              | Round                 | CRI value     | >80                   | Mounting depth     | 90,7 mm                    |
| Input voltage     | 220-240V              | Driver        | Incl. internal driver | Connection type    | Terminal block             |
| Power             | 9 Watt                | Power factor  | >0.90                 | Housing material   | Aluminium (thermal coated) |
| Luminous flux     | 650 Lm                | Beam angle    | 40°                   | Housing color      | White                      |
| Color temperature | 4000K                 | Adjustable    | No                    | Material cover     | PC                         |
| Light color       | Natural white         | IP rate       | IP44                  | Color cover        | Clear                      |
| Dimming method    | Triac                 | Mounting      | Recessed              | Certification mark | CE, RoHS                   |
| LED type          | SMD 2835              | Diameter      | Ø 103 mm              | Warranty           | 3 years                    |
| Lifetime          | L70B50 (44.000 hours) | Mounting hole | Ø 90 mm               |                    |                            |

