



## EUROSTANDARD PLUS - RECESSED

Eurostandard Plus track from the Targetti collection.  
System is a 3 phase mixed system with two additional conductors intended to manage a general data signal (for example DALI, DMX).  
Electrified track in three lengths in extruded anodized aluminum or in extruded painted aluminium.  
Conductors in copper insulated in PVC.

### Installation

There are three possible installation systems: directly on false ceiling (using the needlepoints on the track and the suspension kit), on ceiling using a metal clip or hanging by a mounting kit.

### Power supply


Frequency: 50 Hz.  
Rated current and voltage: L1/L2/L3/N/ground 16A/440V + D+/D- 2x1A/50V FELV AC (DALI).  
Phase / phases power: 3,6kVA / 10,8kVA.



### Characteristic data

Input	230-280 Vac	LED Warranty	G5h24	Color	Black	
-------	-------------	--------------	-------	-------	-------	--

### Dimensional characteristics



L	3000 mm
---	---------

### Electrical characteristics

Input voltage	230-280 Vac
---------------	-------------

### Other Infotech

ENEC	Yes
------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2011/65/EU * RoHS 2012/19/EU * RAEE 2015/863 * Amending RoHS	
--	--

## Logistics data

Item net weight	3400 gr
Barcode single item	8011905992569
Minimum order quantity	1