



Connection box | 3 way | IP65



, delivered with 3 lever connections.	
142-011	
17-01-2024	
Tronix Lighting	
Installation materials	
EG000048 - Connection material (electrotechnical)	
EC002600 - Box/housing for surface mounting on the wall/ceiling	
Box/housing for surface mounting on the wall/ceiling, Cable box, Cable junction box for light pole, Carton, Cross box, Distributor, Distributor box, Distributor enclosure, Earthing arrangements	



Page: 1/3















Feature

Max. conductor cross section:	2.5 mm ²	Colour:	Other
Equipped with:	Other	Degree of protection (IP):	IP65
Shape:	Rectangular	Degree of protection (NEMA):	3
Mounting method:	Universal	Cover model:	Mounting cover
Mounting in the soil:	No	Transparent cover:	Yes
Mounting under water:	No	Cover attachment:	Screwed
For tube diameter:	16 mm	Castable:	Yes
Inlet from the rear:	No	With casting compound:	No
Length:	115 mm	Sealable:	No
Width:	75 mm	Rated insulation voltage Ui:	450 V
Depth:	36 mm	Circuit integrity:	None
Diameter:	0 mm	With screening:	No
Tackable:	No	Weatherproof:	Yes
Number of inlets:	3	Operating temperature:	-20 ~ 70 °C
Type of housing feed-through:	Thread and closing membrane	Explosion-tested version:	No
Material:	Plastic	For Ex-zone gas:	None
Halogen free:	Yes	For Ex-Zone dust:	None
Surface protection:	Untreated		

Packaging data


120 gr
72 mm
40 mm
115 mm
9405920090

Page: 2/3















Page: 3/3

guided by light







tronixlighting.com