



EUROSTANDARD PLUS - RECESSED

Eurostandard Plus track from the Targetti collection.
System is a 3 phase mixed system with two additional conductors intended to manage a general data signal (for example DALI, DMX).
Electrified track in three lengths in extruded anodized aluminum or in extruded painted aluminium.
Conductors in copper insulated in PVC.

Installation

There are three possible installation systems: directly on false ceiling (using the needlepoints on the track and the suspension kit), on ceiling using a metal clip or hanging by a mounting kit.

Power supply

Frequency: 50 Hz.
Rated current and voltage: L1/L2/L3/N/ground 16A/440V + D+/D- 2x1A/50V FELV AC (DALI).
Phase / phases power: 3,6kVA / 10,8kVA.

230-280
Vac




G5h24

Characteristic data

Input	230-280 Vac	LED Warranty	G5h24	Color	White	
-------	-------------	--------------	-------	-------	-------	--

Dimensional characteristics



L	3000 mm
---	---------

Electrical characteristics

Input voltage	230-280 Vac
---------------	-------------

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2011/65/EU * RoHS 2012/19/EU * RAEE 2015/863 * Amending RoHS	
--	--

Logistics data

Item net weight	3400 gr
Barcode single item	8011905992583
Minimum order quantity	1