



## "T" JOINT EXTERNAL POLARITY

Eurostandard Plus track from the Targetti collection.  
 System is a 3 phase mixed system with two additional conductors intended to manage a general data signal (for example DALI, DMX).  
 Electrified track in three lengths in extruded anodized aluminum or in extruded painted aluminium.  
 Conductors in copper insulated in PVC.

### Installation

There are three possible installation systems: directly on false ceiling (using the needlepoints on the track and the suspension kit), on ceiling using a metal clip or hanging by a mounting kit.

### Power supply

Frequency: 50 Hz.  
 Rated current and voltage: L1/L2/L3/N/ground 16A/440V + D+/D- 2x1A/50V FELV AC (DALI).  
 Phase / phases power: 3,6kVA / 10,8kVA.

### Characteristic data

|       |       |  |  |  |  |
|-------|-------|--|--|--|--|
| Color | White |  |  |  |  |
|-------|-------|--|--|--|--|

### European Directives

|  |  |
|--|--|
| 2011/65/EU * RoHS<br>2012/19/EU * RAEE<br>2015/863 * Amending RoHS |  |
|--|--|

### Logistics data

|                        |               |
|------------------------|---------------|
| Barcode single item    | 8011905992873 |
| Minimum order quantity | 1             |