

2024-6-20 | Data subject to change without notice



## Reflector downlight eco | black | Ø174mm | 20W | 3-CCT

Article number: 136-197

This reflector downlight can be placed in various spaces such as offices, living spaces, schools, hotels and other public spaces, due to the simple adjustment of light color.

### Features

- High quality external driver with optimum heat regulation
- For recessed installation
- Plug & Play due the europlug
- Adjustable by a CCT switch into the color temperatures 3000K, 4000K and 6000K
- Long service life of 40,000 hours

### Specifications

|                   |                                                                   |               |                       |                    |           |
|-------------------|-------------------------------------------------------------------|---------------|-----------------------|--------------------|-----------|
| Type              | Round                                                             | CRI value     | >80                   | Mounting depth     | 90 mm     |
| Input voltage     | 220-240V                                                          | Driver        | Incl. external driver | Cable length       | 120 cm    |
| Power             | 20 Watt                                                           |               | (not dimmable)        | Connection type    | Europlug  |
| Luminous flux     | 2000 Lm                                                           | Power factor  | >0.90                 | Housing material   | Aluminium |
| Color temperature | 3-CCT                                                             | Beam angle    | 50°                   | Housing color      | Black     |
| Light color       | Warm white, natural white and cold white (3000K, 4000K and 6000K) | Adjustable    | No                    | Material cover     | PC        |
|                   |                                                                   | IP rate       | IP20                  | Color cover        | Clear     |
|                   |                                                                   | Mounting      | Recessed              | Certification mark | CE, RoHS  |
|                   |                                                                   | Diameter      | Ø 174 mm              | Warranty           | 5 years   |
|                   |                                                                   | Mounting hole | Ø 145 mm              |                    |           |
| Dimming method    | Optional                                                          |               |                       |                    |           |
| LED type          | SMD2835                                                           |               |                       |                    |           |
| Lifetime          | L70B50 (40.000 hours)                                             |               |                       |                    |           |

