

# ONTEC G E1P 301 M DT W TM-OG.EPDTM300W



No: 03A23



No: 4420/2021  
Valid until:  
05.09.2026



No: 88-128652  
Valid until:  
24.06.2025



No:  
B\_BK\_60212\_0267  
Valid until:  
30.06.2026



No: 03A23



No: 2247418.02-  
UAE  
Valid until:  
24.06.2025



No: 03A23



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>ONTEC G</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Colour structure	<b>matte , satin, smooth</b>
Version	<b>DATA</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK05</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram included	<b>yes</b>
Pictogram dimensions	<b>125x125 mm</b>
Evacuation sign dimensions	<b>250x125 mm</b>
Pictogram type	<b>foil</b>
Graphic number	<b>K6</b>
Pictogram logo	<b>TM Technologie</b>
Luminous flux	<b>&gt;300 cd/m<sup>2</sup></b>
Colour temperature	<b>5700 K</b>
Light source	<b>LED</b>
Maximum light power	<b>1.8 W</b>
LED lifetime	<b>50000 h</b>
Minimum temperature	<b>10 °C</b>
Maximum temperature	<b>35 °C</b>
Battery	<b>LiFePO4/C 6.4V 1.5Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>251 mm x 29 mm x 198 mm</b>

