



# **DECO LED TECNO VINTAGE TRASPARENT ROUND**

**Typology**Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

#### Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

#### Material

Glass bulb.

#### Notes

Do not use with dimmers except if otherwise indicated.







15000 h L70B50

IP20



-25°C +35°C





Data sheet code: LFP454830





# **Characteristic data**

Power	4 W	Beam	320°	Input	220-240 Vac	Base	E14
IP	20	Flux	470 lm	PF	0.5	Tc	3000 K
Ra	80	LED Warranty	G2				

### **Dimensional characteristics**



Ø	45 mm
Н	78 mm



Data sheet code: LFP454830



# Lighting and photometric features

Beam opening	320°
Flux	470 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

# **Electrical characteristics**

Rated power	4 W
Input voltage	220-240 Vac
Frequency	50 Hz
Power factor (PF)	0.5
Input current	0.04 A
Weighted energy consumption	4 kWh/1000h
Energy efficiency class	E
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	40
Operating position	360°

# **LED** Warranty

(	52	Up to 2 years
		(4000h/year) *4000h = 11h a day x 365 days.
		Without limitations on the duration of use for the first year, provided the observance of
		the installation conditions.

# **Logistics data**

Item net weight	20 gr
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

