



# **DECO LED TECNO VINTAGE TRASPARENT ROUND**

**Typology**Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

# Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

## Material

Glass bulb.

### Notes

Do not use with dimmers except if otherwise indicated.









15000 h L70B50

IP20

E14

-25°C +35°C



Data sheet code: LFP450627-D







# **Characteristic data**

Power	6 W	Beam	320°	Dimmable	Yes	Input	220-240 Vac
Base	E14	IP	20	Flux	806 lm	PF	0.5
Tc	2700 K	Ra	80	LED Warranty	G2		

# **Dimensional characteristics**

Ø	45 mm	
Н	85 mm	

# Lighting and photometric features

Beam opening	320°
Flux	806 lm
CCT nominal colour temperature	2700 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Data sheet code: LFP450627-D



# **Electrical characteristics**

Rated power	6 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Power factor (PF)	0.5
Input current	0.04 A
Weighted energy consumption	6 kWh/1000h
Energy efficiency class	E
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	60
Operating position	360°

# **LED Warranty**

62	Up to 2 years
	(4000h/year) *4000h = 11h a day x 365 days.
	Without limitations on the duration of use for the first year, provided the observance of
	the installation conditions.

# **Logistics data**

-	
Item net weight	20 gr
Barcode single item	8011905326111
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

