

Data sheet code: LFC374830



DECO LED TECNO VINTAGE TRANSPARENT CANDLE

Typology Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

Notes

Do not use with dimmers except if otherwise indicated.






Characteristic data

Power	4 W	Beam	320°	Dimmable	No	Input	220-240 Vac
Base	E14	IP	20	Flux	470 lm	PF	0,40
Тс	3000 K	Ra	80	LED Warranty	G2		

Dimensional characteristics



Ø	35 mm
Н	98 mm
H Tolerance	± 3 mm

Technical datasheet

Datasheet 18/06/2024 Page 1 of 2



Data sheet code: LFC374830

Lighting and photometric features

Beam opening	320°
Flux	470 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	4 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,40
Weighted energy consumption	4 kWh/1000h
Energy efficiency class	E
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	40
Operating position	360°

LED Warranty

			Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
--	--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

European Directives	Product standards
2009/125/EC * Ecodesign	CEI EN 55015:2020 (+A11:2020)
2011/65/EU * RoHS	CEI EN 60968:2016
2012/19/EU * RAEE	CEI EN 61000-3-2:2019 (+A1:2021)
2014/30/EU * EMC	CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
2014/35/EU * LVD	CEI EN 61547:2010
2015/863 * Amending RoHS	CEI EN 62031:2021 (+A11:2022)
2017/1369 * Regulation for Energy Labelling	CEI EN 62471:2010
2019/2015 * Regulation for Energy Labelling	IEC/TR 62471-2:2009
2019/2020 * Regulation for Ecodesign	CEI EN 62560:2013 (+A1:2017/+A11:2020)
2021/340 * Amending Reg. Energy Labelling	CEI 34-141:2014
2021/341 * Amending Reg. Ecodesign	

Logistics data

Item net weight	20 gr
Barcode single item	8011905987817
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

