

2024-11-19 | Data subject to change without notice



Downl refl. matt | Ø228mm | black |
3-CCT | 13~25W | EU plug

Article number: 136-138

Due to the pre-settable light color, this downlight is suitable for placement in various areas such as offices, living areas, schools, hotels and other public spaces.

Features

- Very efficient (>130Lm/W)
- For recessed and surface mounted installation (with surface mounting kit)
- Plug&Play due to the europlug
- Adjustable by a CCT switch into the color temperatures 3000K, 4000K en 5700K
- Power adjustable in 13, 16, 18, 20 and 25 watts
- Available in [white](#) and black

Specifications

Type	Round	CRI value	>80	Mounting depth	61 mm
Input voltage	220-240V	Driver	Incl. external	Cable length	200 cm
Power	13/16/18/20/25 Watt		adjustable driver (not dimmable)	Connection type	Europlug
Luminous flux	3265 Lm			Housing material	Aluminium
Color temperature	3-CCT	Power factor	>0.90	Housing color	Black
Light color	Warm white, natural white and cold white (3000K, 4000K and 5700K)	Beam angle	60°	Material cover	PC
		Adjustable	No	Color cover	Transparent
		IP rate	IP54	Certification mark	CE, RoHS
		Mounting	Recessed	Warranty	5 years
Dimming method	Optional	Diameter	Ø 228 mm		
LED type	SMD	Mounting hole	Ø 199 mm		
Lifetime	L90B50 (50.000 hours)				

