


# ITECH W2 05 CBA



Catalog number	TM-IT.W2CBA060W
Application	lighting of the final exit / fire-protection devices
Duration time	-
Operating mode	-
Version	for central battery
Colour	RAL9003
Luminous flux	470 lm
Maximum light power (the luminaire can power the light source with a different power)	4.5 W
Active power	6.4 W
Power supply	210+250 V AC
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	-10-40 °C
Material	PC
Appliance classes	2
IP	IP65
IK	IK06
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
LED Lifetime	50 000 work hour
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





## PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	4,1	9,6
3,0	4,2	10,0
4,0	4,4	10,8
5,0	4,5	11,1
6,0	4,3	11,0
7,0		
8,0		
9,0		
10,0		

