

New 2025 Edition 2>Office & Kitchen

## 38160A/W/V



CCT and Power variable 40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with power variable driver.

Complies with standard EN60598-1 and any other specific standards



### Downloads



### Dimensions



### Gallery



### Accessories





050170

## Physical Specification

Item Group	New 2025 Edition 2
Family	Office & Kitchen
Order Code	38160A/W/V
Colour	White
Material	Aluminium
Diffuser Material	PC
Shape	Rectangular
Length	1200mm
Width	75mm
Height	75mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W-30W-40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	

## Fitting

Input Type

Constant Current

IP Rating

IP20

Light Source

LED built in

LED Type

SMD

## Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

IP Rating

IP20

Dimmable

No

## Illumination Data

Colour Temperature

3000K-4000K-5000K

Lumen Output

3400lm (40W)

Light Efficiency

85lm/W

CRI

90

Illumination Diagram



UGR

19

## Packing Info

Pcs/Carton

12

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

