

## **Product** Datasheet

#### New 2025 Edition 2>Office & Kitchen

### 38150BU/W/V



CCT and Power variable 40W UGR17 Linear system with with 48 LED spots and uplight for suspended installation, ideal for offices.

Complete with 2 x power variable drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions		
°O CE	I	1300mm	I <sup>35mm</sup>

#### Gallery



#### Accessories





050170

050170C/W



#### Related items



38150E/W

#### Physical Specification

Item Group	New 2025 Edition 2
Family	Office & Kitchen
Order Code	38150BU/W/V
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1300mm
Width	35mm
Height	70mm
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

#### **Electrical Characteristics**

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V

Yes
Yes
20W-30W-40W + 16W-20W-25W
IP20
LED built in



Dimmable	No
Cable Length	300cm
F Mark	F
Fitting	
Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in
LED Type	SMD
LED Number	48
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Dimmable	No
Protection	0

#### Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	3800lm (40W) / 1800lm (20W)
Light Efficiency	95lm/W / 90lm/W
CRI	90
Beam Angle	34°/120°

Illumination Diagram	34*
Dark Light	Yes
UGR	17

#### Packing Info



#### Certification & Warranty

Warranty	3 Years
Weee Directive	Yes

# switch to one light!



