



Product Datasheet

New 2025 Edition 2>Wall & Ceiling LED

12120D/B/V



CCT Variable 20W LED surface mounted downlight. IP44.

Supplied with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.














Downloads







Dimensions



Gallery



Physical Specification

Item Group	
Family	
Order Code	
Colour	
Material	
Shape	
Height	

New 2025 Edition 2

Wall & Ceiling LED

12120D/B/V

Black

Aluminium

Circular

80mm

Diameter	130mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
IP Rating	IP44
Light Source	LED built in
LED Type	SMD
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Output	500mA	
IP Rating	IP20	
Dimmable	No	
umination Data		
Colour Temperature	3000K-4000K-5000K	
Lumen Output	2000lm	
Light Efficiency	100lm/W	

90

120°

19

CRI

UGR

Packing Info

Beam Angle

Illumination Diagram

Pcs/Carton 30

Certification & Warranty

Warranty 5 Years

Weee Directive Yes

switch to one light!

