



PS36 | IP44 | White | String | 3m | 30led | 3000K WW



| | |
|-----------------|--|
| Article number: | 018-541 |
| CHANGED_LAST: | 18-08-2022 |
| Brand: | Tronix Lighting |
| Type: | String Lights 3M - Connectable |
| ETIM Group: | EG000027 - Luminaires |
| ETIM Classes: | EC002761 - Festive lighting |
| SYNONYM: | Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set |





Feature

| | | | |
|---|---|--|-------------------------|
| Model: | Chainlight | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Number of light centres: | 30 | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Lamp type: | LED not exchangeable | Constant light output (CLO): | No |
| With light source: | Yes | Degree of protection (IP): | IP65 |
| Colour: | White | Protection class: | III |
| Voltage type: | DC | Fire resistance according to UL94: | C |
| Nominal voltage: | 36 ~ 36 V | Colour of light: | White |
| Connected load: | 2 W | Width: | 0 mm |
| Battery power supply: | No | Height/depth: | 0 mm |
| Suitable for outdoor use: | Yes | Total length: | 3 m |
| With power bridge: | No | Diameter: | 0 mm |
| Connectable: | Yes | Type of wiring: | Through wiring included |
| Type of control gear: | LED operating device voltage-controlled | Number of poles: | 2 |
| Exchangeable control gear: | No | Conductor cross section: | 0.5 mm ² |
| Energy efficiency class of the built-in lamp: | A++, A+, A (LED) | Connection type: | Other |
| Rated life time L70/B50 at 25 °C: | 20000 h | commercial, christmas or both: | NA |

Packaging data

| | |
|--------------|------------|
| Weight | 200 gr |
| Width | 80 mm |
| Height | 60 mm |
| Length | 165 mm |
| Customs code | 9405310000 |

