



PS36 | IP65 | Transp. | Icicle | 2x0,4m | 92led | 2400K WW+



|                 |  |
|-----------------|--|
| Article number: | 018-209  |
| CHANGED_LAST:   | 21-06-2022   |
| Brand:          | Tronix Lighting  |
| Type:           | Icicle Light 2M x 80CM   |
| ETIM Group:     | EG000027 - Luminaires  |
| ETIM Classes:   | EC002761 - Festive lighting  |
| SYNONYM:        | Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set |





## Feature

|   |   |  |                         |
|---|---|--|-------------------------|
| Model:  | Curtain light                           | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 %                     |
| Number of light centres:                      | 92                                      | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):      | 0 %                     |
| Lamp type:                                    | LED not exchangeable                    | Constant light output (CLO):   | No                      |
| With light source:                            | Yes                                     | Degree of protection (IP):   | IP65                    |
| Colour:                                       | Other                                   | Protection class:  | III                     |
| Voltage type:                                 | DC                                      | Fire resistance according to UL94:   | C                       |
| Nominal voltage:                              | 36 ~ 36 V                               | Colour of light:   | White                   |
| Connected load:                               | 7.6 W                                   | Width:   | 0 mm                    |
| Battery power supply:                         | No                                      | Height/depth:  | 400 mm                  |
| Suitable for outdoor use:                     | Yes                                     | Total length:  | 2 m                     |
| With power bridge:                            | No                                      | Diameter:  | 0 mm                    |
| Connectable:                                  | Yes                                     | Type of wiring:  | Through wiring included |
| Type of control gear:                         | LED operating device voltage-controlled | Number of poles:   | 2                       |
| Exchangeable control gear:                    | No                                      | Conductor cross section:   | 0.5 mm <sup>2</sup>     |
| Energy efficiency class of the built-in lamp: | A++, A+, A (LED)                        | Connection type:   | Other                   |
| Rated life time L70/B50 at 25 °C:             | 20000 h                                 | commercial, christmas or both:   | NA                      |

## Packaging data

|              |            |
|--------------|------------|
| Weight       | 560 gr     |
| Width        | 80 mm      |
| Height       | 120 mm     |
| Length       | 220 mm     |
| Customs code | 8544429090 |

