



## Panel | 60\*120 | 20/25/32/36/40W | 3-CCT | EU plug

Article number: 173-042

This LED panel is suitable for installation in (suspended) ceilings of 60x120 cm. A hanging up method is also possible, using a surface mounting kit. The smooth, soft and flicker-free light spread by the LED panel, makes it extremely suitable for use in offices and retail spaces, but also think of indoor lighting of schools and any other public spaces.

### Features

- High quality external driver with optimum heat regulation
- Flicker-free (1%)
- Plug & Play due connection cable and euro plug
- High light efficiency of >165 Lm/W
- Adjustable power for 20, 25, 32, 36 and 40 Watts
- Adjustable by a CCT switch in the color temperatures 3000K, 4000K and 5700K
- 5 year warranty

### Specifications

Size	60 x 120 cm	CRI value	>80	Height	11 mm
Input voltage	220-240V	UGR value	UGR>19	Cable length	200 cm
Power	20/25/32/36/40 Watt	Driver	Incl. external driver	Connection type	Europlug
Luminous flux	5765 Lm	Power factor	>0.97	Housing material	Aluminium
Luminous efficiency	>150 Lm/W	Flicker-free	Yes 1%	Housing color	White (powder coating)
Color temperature	3-CCT	Beam angle	120°	Material diffuser	PMMA (Polymethyl methacrylate)
Light color	Warm white, natural white and cold white (3000K, 4000K and 5700K)	IP rate	IP20	Lighting method	Edge-lit
Dimming method	Not dimmable	Length	1195 mm	Certification mark	CE, RoHS
Lifetime	L80B50 (50.000 hours)	Width	595 mm	Warranty	5 years

