

LED strip | COB | 10W/m | IP20 | 2200K | free cuttable



This COB LED strip has no visible LED interruptions. This makes it possible to use the COB strip in undeap aluminium profiles with a clear cover. With 3M adhesive tape on the back for easy installation.

Features

- High flexibility with a minimum bending radius of 10 mm
 Free to cut all over the line
- Beam angle 180°
- High color rendering index CRI>90
- IP20 for indoor use

Article number:	127-169
CHANGED_LAST:	04-03-2024
Brand:	Tronix Lighting
Туре:	LED strips
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC002706 - Light ribbon-/hose/-strip
SYNONYM:	LED, LED strip, LED-light ribbon-/hose/-strip, LED-strip, Light ribbon-/hose/-strip, Single LED



Page: 1/3









Feature

Model:	Strip	Colour rendering index CRI:	90-100
Mounting method:	Surface mounting/recessed mounting	Colour of light adjustable:	No
Lamp type:	LED not exchangeable	Luminous flux adjustable:	Continuously variable
Number of nodes per meter:	480	Beam angle adjustable:	No
Lamp power per meter:	10 W	Width:	8 mm
Lamp power per foot:	0 W	Height/depth:	2 mm
Luminous flux per meter:	920 lm	Length:	5000 mm
Voltage type:	DC	Diameter:	0 mm
Lamp voltage:	24 ~ 24 V	Lowest bending radius:	10 mm
Beam angle:	180 °	Length of particular segments:	0 mm
Suitable for dimmer:	Yes	With end piece:	No
Exchangeable control gear:	Yes	With connection set:	No
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	With protective cover:	No
Rated life time L70/B50 at 25 °C:	54000 h	Self-adhesive:	Yes
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Type of wiring:	Through wiring included
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Number of poles:	2
Degree of protection (IP):	IP20	Conductor cross section:	0.5 mm²
Degree of protection (NEMA):	1	Connection type:	Other
Protection class:	Ш	Compatible with Apple HomeKit:	No
Max. system power:	75 W	Compatible with Google Assistant:	No
Colour of light:	White	Compatible with Amazon Alexa:	No
Constant light output (CLO):	No	IFTTT support available:	No
Colour temperature:	2200 ~ 2200 K		

Packaging data


Weight	120 gr
Width	220 mm
Height	10 mm
Length	210 mm
Customs code	9405990090




















Page: 3/3

