

2025-5-8 | Data subject to change without notice



Panel | 30*60 | 6/8/10/13/15W | 3-CCT | EU plug

Article number: 173-032

This LED panel is suitable for installation in (suspended) ceilings of 30x60 cm. A hanging up method is also possible, using suspension cables or a surface mounting kit. The smooth, soft and flicker-free light spread by the LED panel, makes it extremely suitable for use in offices and retail spaces, but also think of indoor lighting of schools and any other public spaces.

Features

- High quality external driver with optimum heat regulation
- Flicker-free (1%)
- Plug & Play due connection cable and euro plug
- High light efficiency of >140 Lm/W
- Adjustable power for 6, 8, 10, 13 and 15 Watts
- Adjustable by a CCT switch in the color temperatures 3000K, 4000K and 5700K
- 5 year warranty

Specifications

Size	30 x 60 cm	CRI value	>80	Height	11 mm
Input voltage	220-240V	UGR value	UGR>19	Cable length	200 cm
Power	6/8/10/13/15 Watt	Driver	Incl. external driver	Connection type	Europlug
Luminous flux	2037 Lm	Power factor	>0.97	Housing material	Aluminium
Luminous efficiency	>140 Lm/W	Flicker-free	Yes 1%	Housing color	White (powder coating)
Color temperature	3-CCT	Beam angle	120°	Material diffuser	PMMA (Polymethyl methacrylate)
Light color	Warm white, natural white and cold white (3000K, 4000K and 5700K)	IP rate	IP20	Lighting method	Edge-lit
		Length	595 mm	Certification mark	CE, RoHS
		Width	295 mm	Warranty	5 years
Dimming method	Not dimmable				
Lifetime	L80B50 (50.000 hours)				

