

2026-1-14 | Data subject to change without notice



LED panel | 60*60 | 25W | 3-CCT | excl. driver

Article number: 173-002

This LED panel is suitable for installation in (suspended) ceilings of 60*60 cm. A hanging up method is also possible, using suspension cables or a surface mounting kit. The smooth, soft and flicker-free light spread by the LED panel, makes it extremely suitable for use in offices and retail spaces, but also think of indoor lighting of schools and any other public spaces.

This panel is delivered excl. driver, so it can be made dimmable. To make it dimmable, you need the following:

Single color:

- Connector set 173-096;
- Triac, Dali, 1-10V or RF dimmable driver (find related products, set to 650mA);
- Europlug or GST-plug.

Tunable white:

- Connector set 173-095;
- Dali or RF dimmable driver that is suitable for tunable white (find related products, set to 650mA);
- Europlug or GST-plug.

Specifications

Size	60 x 60 cm	CRI value	>80	Height	25 mm
Input voltage	38V	UGR value	UGR>19	Connection type	Optional
Power	25 Watt	Driver	Excl. external driver	Housing material	Aluminium
Luminous flux	3750 Lm	Power factor	>0.9	Housing color	White
Luminous efficiency	>150 Lm/W	Flicker-free	Yes 1%	Material diffuser	PS (Polystyrene)
Color temperature	3-CCT	Beam angle	120°	Lighting method	Back-lit
Light color	3000K, 4000K and 5700K	IP rate	IP20	Certification mark	CE, RoHS
Dimming method	Optional	Length	595 mm	Warranty	5 years
Lifetime	L90B10 (50.000 uur)	Width	595 mm		

